



# TECHNICAL DATA SHEET

## ENGINEERED WOOD FLOOR - OAK



### Features

Material:	Luxury SPC
Coating:	Double UV Laquer
Locking System:	Uniclick
Packaging:	Cardboard box
Finish:	Ultra Shield Protection



### Features

Version	Total thickness (mm)	Wear layer (MIL)	IXPE Pad (mm)	Width (in)	Length (in)	m <sup>2</sup> /box	Lbs/box	boxes/pallet
6.5mm x 9"	6.5mm	22MIL	1.5mm	9"	RL up to 60"	22.50	50	52
6.5mm x 9"	6.5mm	22MIL	1.5mm	9"	RL up to 60"	22.83	50	60
6.5 mm x 6"	6.5mm	22MIL	1.5mm	6"	RL up to 36"	18.00	38	66
<b>Tolerances:</b>	+- 0,6%			+- 0,2%	+- 0,1%			

### Packaging

<sup>a</sup> 140mm width only available in the Volga color (all grades) and Epic grade.  
<sup>b</sup> Only for the Riviera collection.

### Finishing

Grade	Eternal	Traditional	Epic
Gloss	Matte 5-10%	Matte 5-10%	Matte 5-10%
Pore	Open	Open	Open
Varnish	UV	UV	UV
Texture	Wire brushed	Wire brushed / Not brushed <sup>c</sup>	Wire brushed / Not brushed <sup>c</sup>

<sup>c</sup> The Volga color in the Traditional and Epic grades has the 'Not brushed' texture.

### Maintenance, conservation and cleaning

Periodically the wooden floors should be cleaned by using an appropriate liquid suitable for varnished floors. Do not use chemical products, with an ammonia constituent and avoid, at all costs, cleaning with damp cloths and wet mops. After cleaning the floor, you can use a cleaning product and another revitalizing product, both suitable for wooden floors. Floor protectors should be placed on the bottom of furniture so they will not damage the floor.



Light commercial use



Residential use



Eco-friendly



VOC free



Quality guaranteed



Greater stability



High durability



Suitable for underfloor heating



UV radiation protection



Impact resistant



Allergy friendly



Scratch-resistant



Slip resistant



Easy to clean



Easy stain removal

### Types of installation



Floating



Glue down



Nail down

### Additional information

Installation / assembly information printed on the box.

### Standards

EN 14342 - Wood flooring Characteristics, evaluation of conformity and marking

NP EN 13489 - Wood flooring and parquet - Multi-layer parquet elements

NP EN 13756 - Wood flooring and parquet - Terminology

NP EN 350 - Durability of wood and wood - based products

EN 13647 - Wood flooring and wood panelling and cladding

EN 335 - Durability of wood and wood-based products

Lacey Act Compliant / CE / European Timber Regulation / CARB Compliant / CDPH Standard Compliant / National Wood Floors Association



USA +1 888.505.2827  
 purchasing@ribadao.com  
 www.ribadaoamericas.com